



# Green<sup>®</sup>

Premium Performance



## EYE NEVER SLEEPS ...

[www.green4tech.net](http://www.green4tech.net)

► Fixed Lens Dome Camera



**GDPL20**

IR LED: 14 $\mu$  x 18PCS  
IR RANGE: 20M  
Lens : 3.6mm  
(2.8mm or 6mm optional)  
Housing Material: Plastic



**GDTH20**

IR LED: 42 $\mu$  x 2PCS  
IR Range: 20M  
Lens: 2.8mm/F2.0  
Housing Material: Plastic



**GDTB30**

IR LED: 20 $\mu$  X 2PCS  
IR Range: 30M  
Lens: 3.6mm/F2.0  
Housing Material: Plastic



**GDTD20**

IR LED: 16 $\mu$  X 8PCS  
IR Range: 20M  
Lens: 3.6mm/F2.0  
Housing Material: Plastic



**GDSH20**

IR LED: 14 $\mu$  X 18PCS  
IR Range: 20M  
Lens: 3.6mm/F2.0  
Housing Material:  
Vandalproof, Metal



**GDSDL20**

IR LED: 14 $\mu$  X 18PCS  
IR Range: 20M  
Lens: 3.6mm/F2.0  
(2.8mm optional)  
Housing Material:  
VANDalproof, Meta



**GDTC20**

IR LED: 12 $\mu$  X 12PCS  
IR Range: 20M  
Lens: 3.6mm/F2.0  
Housing Material:  
Vandalproof, Metal



**GDTF20**

IR LED: 12 $\mu$  X 12PCS  
IR Range: 20M  
Lens: 3.6mm/F2.0  
Housing Material:  
Vandalproof, Metal

# 5MP Dome 4IN1 HD IR 30m

## WISDOM EYE CAMERA

4 in 1 Wisdom eye is able to support TVI up to 5M, AHD up to 5M, CVI up to 4M and CVBS



IR-CUT



UTC



OSD



4 IN 1



► Varifocal Lens Dome Camera



**GDVRN20**

IR LED: 16 $\mu$  X 8PCS  
 IR Range: 20M  
 Lens: 2.812-mm  
 Manual Zoom  
 Housing Material: Plastic



**GDVSHR30**

IR LED: 14 $\mu$  X 24PCS  
 IR Range: 30M  
 Lens: 2.812-mm  
 Manual Zoom  
 Housing Material:  
 Vandalproof, Metal



**GDVSHT30**

IR LED: 14 $\mu$  X 24PCS  
 IR Range: 30M  
 Lens: 2.8-12mm  
 Manual Zoom  
**Motor Zoom &  
 Auto Focus (Optional)**  
 Housing Material:  
 Vandalproof, Metal  
**Starvis Back-illuminated  
 (Optional)**



**GDVDH20**

IR LED: 14 $\mu$  X 18PCS  
 IR Range: 20M  
 Lens: 2.8-12mm Manual Zoom  
 Housing Material:  
 Vandalproof, Metal  
 Water resistance: IP66

► Fixed Lens Weatherproof Bullet Camera



**GBCP20**

IR LED: 14 $\mu$  X 18PCS  
 IR Range: 20M  
 Lens: 3.6mm  
**(2.8mm or 6mm optional)**  
 Housing Material: Plastic  
 Water resistance: IP66



**GBCP25**

IR LED: 14 $\mu$  X 20PCS  
 IR Range: 25M  
 Lens: 3.6mm/F2.0  
 Housing Material: Metal  
 Water resistance: IP66



**GBCD20**

IR LED: 14 $\mu$  X 18PCS  
 IR Range: 20M  
 Lens: 3.6mm/F2.0  
**(2.8mm optional)**  
 Housing Material: Metal  
 Water resistance: IP66



**GBCW30**

IR LED: 42 $\mu$  X 2PCS  
 IR Range: 30m  
 Lens: 2.8mm/F2.0  
 Housing Material: plastic  
 Water resistance: IP66

# STARLIGHT

**Green**  
Premium Performance

Make Darkness Totally Visible

HD 4 IN 1 Starlight Camera



STARLIGHT



MOTION DETECTION



1080P HD



No black and white image at night any more. All can be captured in full color to make sure you can have a sound sleep.



▶ Fixed Lens Weatherproof Bullet Camera



**GBCA25**

IR LED: 42μ x 2PCS  
 IR Range: 25M  
 LenS: 3.6mm/F2.0  
 (2.8mm Optional)  
 Housing Material: Plastic  
 Water Resistance: IP66



**GBRD30**

Weatherproof IP66  
 IR LED: 42μ x 2PCS  
 IR Range: 30M  
 Lens: 3.6mm  
 Housing Material: Metal  
 Water Resistance: IP66



**GBBB90**

Weatherproof IP66  
 IR LED: 42μ x 2PCS  
 IR Range: 60mm/F1.2  
 (8mm/F1.2 Optional)  
 Lens: 3.6mm  
 Housing Material: Metal  
 Water Resistance: IP66  
 Starvis Back-illuminated (Optional)  
 Starlight (Optional)

▶ Varifocal Lens Weatherproof Bullet Camera



**GBVBYT40**

IR LED: 14μ X 30PCS  
 IR Range: 40M  
 Lens: 2.8-12mm Manual Zoom  
 Housing Material: Metal  
 Water resistance: IP66

▶ Varifocal Lens Weatherproof Bullet Camera



**GBVA60**

IR LED: 14μ X 48PCS  
 IR Range: 60M  
 Lens: 2.8-12mm Manual Zoom  
 Motor Zoom & Auto Focus (Optional)  
 Housing Material: Metal  
 Water resistance: IP66  
 Starvis Back-illuminated (Optional)

▶ PTZ & PAN Weatherproof Speed Dome Camera



**GPT5AM18X200NS**

5" Medium Speed PTZ Dome Camera  
 3 IN 1: AHD / HD-TVI / CVBS  
 1/2.9" SONY 2.1MP CMOS Sensor  
 IR LED: □42 X 6PCS  
 IR Range: 60M  
 Lens: 18x Optical Zoom (f=4.7mm-84.6mm)  
 Rotation Range: 360°  
 Rotation Speed: 30°/sec.  
 Communication Protocol: Pelco-D, Pelco-P  
 Communication interface: RS485  
 Baud Rate: 1200/2400/4800/9600bps  
 Housing Material: Metal  
 Water resistance: IP66  
 Lightning Protection:  
 Transient Voltage 6000V



**GPT7FH18X200NS**

7" High Speed PTZ Dome Camera  
 3 IN 1: AHD / HD-TVI / CVBS  
 1/2.9" SONY 2.1MP CMOS Sensor  
 IR LED: □42 X 8PCS  
 IR Range: 120M  
 Lens: 18x Optical Zoom (f=4.7mm-84.6mm)  
 Rotation Range: 360°  
 Rotation Speed: 60°/sec  
 Communication Protocol: Pelco-D, Pelco-P  
 Communication interface: RS485  
 Baud Rate: 1200/2400/4800/9600bps  
 Housing Material: Metal  
 Water resistance: IP66  
 Lightning Protection:  
 Transient Voltage 6000V



**GPVBKHTC2005XES**

Pan/Zoom Bullet Camera  
 3IN1: AHD/HD-TVI/CVBS  
 1/2.9" SONY 2.1MP CMOS Sensor  
 IR LED : 35μx4PCS  
 IR Range: 30m  
 Lens : 2.7-13.5mm Manual Zoom  
 Motor Zoom & Auto Focus (Optional)  
 Rotation Range : 160°  
 Rotation Speed : 30°/sec  
 Housing Material : Metal  
 Water Resistance : IP66

# 5X OPTICAL ZOOM

TO NOT MISS EVERY DETAIL



Focusing towards the picture details presented is vital, but the intelligent optical focus proofreading also makes manipulation for equipment more convenient. However, the traditional camera is only able to employ fixed focus model to set up the picture.

■ 2.7MM--13.5MM FOCAL LENGTH   ■ F4.0 APERTURE LENS   ■ AUTO ZOOM

 **Green**<sup>®</sup>  
Premium Performance

CVI

TVI

AHD

CVBS



► 5 in 1 XVR



**GXVR2604N**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **4CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 4CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p/960H  
 Interface: PTZ, 2xUSB2.0, 1XRJ45 10/100,1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVR2608N**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **8CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 4CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p/960H  
 Interface: PTZ, 2xUSB2.0, 1XRJ45 10/100,1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVR2616N**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **16CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 2CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p/960H  
 Interface: PTZ, 2xUSB2.0, 1XRJ45 10/100,1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVRA2116**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **16CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 4CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p/960H  
 Interface: PTZ, 2xUSB2.0, 1XRJ45 10/100,2 SATA Hard Disk Interface (Up to 12TB)  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVRT2116**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **16CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 4CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p/960H  
 Interface: PTZ, 2xUSB2.0, 1XRJ45 10/100,2 SATA Hard Disk Interface (Up to 12TB)  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVRL3132**

Signal Type: AHD / CVI / TVI2.0 / CVPS / IP  
 Video Input: BNC **32CH In**  
 Video Output: VGA 1CH Out / HDMI2.0 1CH Out  
 Audio Input/Output: RCA 12CH In / 1CH Out  
 Compression Method: H.264  
 Preview Resolution: 1080p/720p  
 Interface: PTZ, 2xUSB2.0, **1xRJ45 10/100/1000,8 SATA Hard Disk Interface(Up to 48TB) + 1 E-SATA Interface(Up to 6TB)**  
 Support Remote View by Mobilephone (iOS, Android, Windows)



**GXVRD2104**

Signal Type : AHD / CVI / TVI / IP / ANALOG  
 Video Input : **4CH** (1920 × 1080P / 1280 × 1024 / 1280 × 720 / 1024 × 768 )  
 Video Output : 1 HDMI,1 VGA, 1CVBS  
 Audio Input/Output : 4Channel, RCA in / 4Channel, RCA out  
 Compression Method : H.264  
 Interfaces : PTZ , 2 USB 2.0 , 1 RJ45 10M/100M, 1 Sata Interfaces Hard Disk , + 2.5"/3.5" SATA, (Up To 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



**GXVRD3108**

Signal Type : AHD / CVI / TVI / IP / ANALOG  
 Video Input : **8CH** (1920 × 1080P / 1280 × 1024 / 1280 × 720 / 1024 × 768 )  
 Video Output : 1 HDMI,1 VGA, 1CVBS  
 Audio Input/Output : 4Channel, RCA in / 1Channel, RCA out  
 Compression Method : H.264  
 Interfaces : PTZ , 2 USB 2.0 , 1 RJ45 1 RJ45 10M/100/1000M, 1 Sata Interfaces Hard Disk , + 2.5"/3.5" SATA, (Up To 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)





# Fisheye Camera

Wireless 360° Panoramic VR Camera



360° VR IP Camera  
to View All Corners

2MP / 4MP / 12MP



Built-in POE



SUPPORT P2P



WIRELESS



MOTION DETECTION



SD CARD



360 FULL VIEW



AUDIO I/O

## ▶ Fixed Lens Weatherproof Bullet IP Cameras



### GBBB90IP

Weatherproof IP66  
 IR LED: 42μ x 6PCS  
 IR Range: 60M  
 Lens: 8mm (5mm or 6mm Optional)  
 PoE: **Optional**  
 Housing Material: Metal  
 (4K Optional)



### GBCV25IP

Weatherproof IP66  
 IR LED: 14μ x 20PCS  
 IR Range: 25M  
 Lens: 3.6mm/F2.0 (2.8mm Optional)  
 PoE: **Optional**  
 Housing Material: Metal



### GBR25IP

Weatherproof IP66  
 IR LED: 42μ x 2PCS  
 IR Range: 30M  
 Lens: 3.6mm/F2.0 (2.8mm Optional)  
 PoE: **Optional**  
 Housing Material: Metal



### GBBY40IP

Weatherproof IP66  
 IR LED: 14μ x 30PCS  
 IR Range: 40M  
 Lens: 3.6mm  
 PoE: **Optional**  
 Housing Material: Metal

## ▶ Fixed Lens Dome IP Camera



### GDSH20IP

Vandalproof IP66  
 IR LED: 14μ x 18PCS  
 IR Range: 20M  
 Lens: 3.6mm/F2.0 (2.8mm Optional)  
 PoE: **Optional**  
 Housing Material: Metal

## ▶ VR Fisheye IP Camera



### GFDE20IP

Fisheye Camera  
 IR LED: 42μ x 3PCS  
 IR Range: 20M  
 Lens: 1.05mm  
 SD Card Slot (Max.64GB)  
 Wifi: IEEE802.11b/g/n  
 WiFi Range: Max.300m  
 Audio: 2-Way Audio  
 Alarm 1Channel Input/Output  
 PoE: Internal  
 SD Card Slot: Support 64Gb  
 Micro SD Card

## ▶ Varifocal Lens Weatherproof Bullet IP Cameras



### GBBQ60IP

Weatherproof IP66  
 IR LED: 42μ x 4PCS  
 IR Range: 40M  
 Lens: 2.7-13.5mm Manual Zoom  
 (Motor Zoom & Auto Focus Optional)  
 PoE: **Optional**  
 Housing Material: Metal

## ▶ Weatherproof Speed Dome IP Camera (PTZ Camera)



### GPT5AM22XHP200SIP

5" Medium Speed Dome Camera  
 1/2.9" SONY 2.1MP CMOS Sensor  
 IR LED: C 42x6PCS  
 IR Range: 60m  
 Lens: 22X Optical Zoom  
 (f=3.9mm-85.5mm)  
 Rotation Range : 360°  
 Rotation Speed : 30°/sec  
 Network protocol: TCP/IP, TTP , NTP  
 , IGMP, DHCP, UDP, SMTP, RTP, RTSP  
 , ARP, DDNS, DNS, PPPoE, P2P  
 Network interface : Built-in RJ45 network  
 interface support 10M/100M IP DATA  
 Housing Material: Metal  
 Water Resistance : IP66  
 Lightning Protection :  
 Transient voltage 6000V

# HIDDEN INFRARED LIGHT

The infrared light of starlight camera isn't light, that you can't find the camera at the night. To avoid the infrared light is too bright, criminal can find the camera far away, so as to avoid the scope of monitoring.

42 $\mu$  x 4PCS  
IR LED

40<sup>m</sup>  
IR range

IR-CUT





### GNVRD2004

IP Camera Input: **4CH** (1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 24MB  
 Recording Resolution: 1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.264  
 Interface: 2xUSB2.0, 1xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRD2009

IP Camera Input: **9CH** (1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 60MB  
 Recording Resolution: 1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.264  
 Interface: 2xUSB2.0, 1xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRD9804

IP Camera Input: **4CH** (4096×2160, 2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 80MB  
 Recording Resolution: 4K/5M/4M/3M 1080P/ 960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.265/H.264  
 Interface: 2xUSB2.0, 1xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRD9809

IP Camera Input: **9CH** (4096×2160, 2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 80MB  
 Recording Resolution: 4K/5M/4M/3M/1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.265/H.264  
 Interface: 2xUSB2.0, 1xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRD9816

IP Camera Input: **16CH** (4096×2160, 2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 80MB  
 Recording Resolution: 4K/5M/4M/3M/1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.265/H.264  
 Interface: 2xUSB2.0, 1xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRD8908POE

IP Camera Input: **16CH** (4096×2160, 2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720)  
**PoE: 8xIndependent 100Mbps PoE Network Interfaces (48V ≤15.4W per Interface)**  
 Incoming Bandwidth: 80MB  
 Recording Resolution: 4K/5M/4M/3M/1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 1CH In / RCA 1CH Out  
 Compression Method: H.265/H.264  
 Interface: 2xUSB2.0, 9xRJ45 10/100, 1 SATA Hard Disk Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)



### GNVRL9364PN

IP Camera Input: **64CH** (4096×2160, 2592x1944, 2048x1536, 1920×1080, 1280×960, 1280×720)  
 Incoming Bandwidth: 300MB  
 Outgoing Bandwidth: 256MB  
 Recording Resolution: 4K/5M/4M/3M/1080P/960P/720P (All Real Time)  
 Video Output: VGA 1CH / HDMI2.0 1CH  
 Audio Input/Output: RCA 16CH In / RCA 4CH Out  
 Compression Method: H.265/H.264  
 Interface: 2xUSB2.0, **1xUSB3.0, 2xRJ45 10/100/1000, 8 SATA Hard Disk Interface (Up to 48TB)**, 1xESATA Interface (Up to 6TB)  
 Support Remote View by Smart Phone (iOS, Android, Windows)

# IP66 METALLIC HOUSING

The camera of IP66 metallic housing and bracket makes it suitable for outdoor use, which is designed with graceful shape and exquisite line.



**Head Office:** 1 Al-Sabak St., from Gesr Al-Sweis St., Heliopolis, Cairo, Egypt.

**Tel.:** (+202) 26388806 (+202) 26388807

**Fax:** (+202) 26388807 **Mobile:** (+2) 01000870074

**Facebook:** [www.facebook.com/Green4tech](http://www.facebook.com/Green4tech) **E-mail:** [info@green4tech.net](mailto:info@green4tech.net)

**Show Room:** 74 Tomanbay St., El-Tahra Palace, El-Zaitoun, Cairo, Egypt

**Tel.:** (+202) 24500118 (+202) 24500119

**Mobile:** (+2) 01000983371

**Website:** [www.green4tech.net](http://www.green4tech.net)