


## PP20H200F

### 2MP Dome HD Camera (Fixed Lens)



#### **FEATURES:**

IR LED: 14 $\mu$  x 18PCS

IR range: 20M

Image Sensor: 1/2.9" CMOS Sensor

Lens: 2.8mm Lens (3.6mm or 6mm Optional)

Camera Type: Coaxial Camera

Signal: 4 in 1 (4 signals switchable TVI/AHD/CVI/CVBS)

Housing: Plastic IP67

Size: 90.5(W) x 80(H) x 80(D)mm

Weight: 300g



CE FC RoHS

## ➤ Datasheet

<b>Camera</b>	
Image Sensor	1/2.9" CMOS Sensor
Image Resolution	2MP
Effective Pixels	1920(H)*1080(V)@30fps/25fps
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/50000Sec; NTSC 1/30-1/50000Sec
S/N Ratio	≥65dB
Minimum Illumination	0.005 Lux/F1.2, 0 Lux with IR
Electronic Shutter	Auto
Scanning System	Progressive Scan
<b>Lens</b>	
Focus Length	Board Lens 2.8mm (3.6mm or 6mm Optional)
Focus Control	Fixed
Lens Type	Fixed
Auto Iris Support	No
<b>Night Vision</b>	
Infrared LED	14μ x 18PCS
Infrared Distance	20M
IR Status	AGC Auto Control
IR Power On	Auto Control
<b>Camera Features</b>	
Starlight	No
Day/Night	Yes
OSD Menu Language	Yes
White Balance	Auto/Manual

Gain Control	Auto
Noise Reduction	Support 3D NR
Picture Adjustment	Yes
WDR	Support DWDR
OSD	Support OSD
UTC	Yes
Dip Switch	No
<b>General</b>	
Housing	Plastic IP67
Bracket	No
Dual Voltage	No
IR Cut Filter	Yes
Heater	No
Audio	No
Operation Temperature	-40°C ~ +60°C RH95% Max
Storage Temperature	-40°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 550mA
Dimension	90.5(W) x 80(H) x 80(D)mm
Weight	300g

## ➤ Dimensions

